


TCPCD40

4.0T ALL-TERRAIN FORKLIFT



Toyota Seat



Attachments



Customize Mast



Optional Engine



Cab



Solid Tire



HIGH PERFORMANCE
HYDRAULIC CYLINDER



POWERFUL ENGINE



LOW FUEL CONSUMPTION
AND HIGH PERFORMANCE



WEAR-RESISTANT TYRE



ULTRA-HIGH SECURITY

PARAMETERS & PERFORMANCE TCPCD40

General				
Model			TCPCD40	
Rated Load Capacity		kg	4000	
Load Center		mm	500	
Dimensions				
Lifting Height		mm	3000	
Free Lifting Height		mm	135	
Fork Size (LxWxT)		mm	1220×125×50	
Mast Tilting Angle(F/R)			6/12	
Length(without fork)		mm	4400	
Overall Width		mm	1980	
Mast Hight After Mast Fall		mm	2195	
Lift Height		mm	4250	
Overhead Guard Height		mm	2300	
Turning Radius		mm	4600	
Front Overhang		mm	700	
Min.Right Angle Channel Width		mm	3000	
Wheelbase		mm	2200	
Track(Front/Rear)		mm	1560/1560	
Ground Clearance	Mast	mm	260	
	Car Center	mm	320	
Performance				
Speed	Travel	Full Load	km/h	20
		No Load	km/h	30
	Lifting	Full Load	mm/s	320
		No Load	mm/s	340
	Lowering	Full Load	mm/s	450
		No Load	mm/s	380
Max.Drawbar Pull		Full/No Load	kg	2600/1520
Max.Gradeability		Full/No Load	%	20/25
Tire				
Front Tire			16/70-20	
Rear Tire			16/70-20	
Weight				
Total Weight		kg	5630	
Power&Transmission				
Battery	Voitage/Capacity		V/AH	24/60
	Model			Yunnei 76kw
Engine	Rated Pover/Speed		KW/rpm	76/2400
	Max.Torque/Speed		N.m/rpm	260-332/1800-2200
Work Pressure		Mpa	18	

